



Catalogue
CATERING
Chapter
COOKING

Model
BM-E910 380-415V 3N

19031538

14/12/2018

ELECTRIC BAIN MARIE, BM-E910

Bain marie are ideal machines to keep the temperature of products such as sauces, stews or garnish. You can either put pans directly on them or you may use Gastronorm containers.

Thanks to the well dimensions and the separating cross bars, it may be used with different GN container types depending on in each machine configuration options.

2 mm stainless AISI-304 steel top with rounded edges for easy cleaning.

Laser cut and automatic welding for a perfect adjustment of sides between modules with square angle finish.

Integrated AISI-304 stainless steel well with rounded edges for easy cleaning.

The well can be configured to fit different Gastronorm containers of different sizes and 150 mm deep. Well dimensions: GN-2x[1/1 + 1/3].

Well capacity: 44 litres.

Standard equipment: 3 crossbars for Gastronorm containers support.

The top is ready to have a water inlet installed to fill the well.

The well can be easily emptied by extracting the overflow tube.

AISI 304 stainless steel resistances outside the well.

Range of temperature between 30 and 90 °C controlled by thermostat.

Safety thermostat.

Water-tight and protecting-support controls.

High temperature protector for the chimney made of enamelled cast iron.


Front access to components.

According to European standards for components and panels temperature, efficiencies and combustion, and sanitary regulations (EN-60335 and EN-203)

IPX5 grade water protection equipment.

DIMENSIONS

X Width	800 mm	X Gross width	840 mm
Y Depth	930 mm	Y Gross depth	1022 mm
Z Height	290 mm	Z Gross height	535 mm
Net Weight	54,0 kg	Gross Weight	73,0 kg
Net volume	0,222 m3	Gross volume	0,459 m3



ELECTRICITY TECHNICAL SPECIFICATIONS



Electric power	6,000 kW
Heating power	6,00 kW
Voltage	380-415V - 3N
Amperage	10A
Electric frequency	50/60Hz

WATER TECHNICAL SPECIFICATIONS



Pressure	H2O: 200-400kPa(2-4bar)
----------	-------------------------



BM-E910



BM-E905



E – Conexión eléctrica
1 – Mando eléctrico
2 – Piloto verde
3 – Piloto ambar

Electrical connection
Electric control
Green pilot
Ambar pilot

