



# FINISHING TOPPER FOR TROUSERS



## T-3000

### FINISHING TOPPER FOR TROUSERS

- Model in centralised version C (without boiler) or stand-alone A (with boiler)
- Trouser topper with pneumatic legs stretcher.
- Pneumatic mannequin to iron trousers, to connect to an external steam source and centralised compressed air, or complete with built-in automatic electric boiler.
- Side waistband stretching device.
- Height-adjustable trouser-stretching carriage and holding clamps made of stainless steel.
- Built-in three-phase fan.
- Air superheater
- Electronic card for the setting of nine ironing cycles in total.
- Ironing cycle which controls steaming time, steam/air time, drying time.
- Three pressure regulators (for leg clamps, waistband stretcher and trouser-stretching carriage).
- Switch for exclusion of the leg-stretching carriage.
- Manual size indicator.
- Mechanical airflow regulator.
- Requires connection to compressed air compressor.
- Electrical connection: 230V 3~ / 400V 3N / 50-60Hz.
- Version C (centralised): model which requires connection to an external steam source. Requires steam connection and return.  
It can be installed with the FAGOR steam generator MAXI-24-22.
- Version A (stand-alone): complete with built-in steam boiler, electrical operation.



TECHNICAL DATA

UNIT.	T-3000 A	T-3000 C
<b>GENERAL DETAILS</b>		
BOILER	YES	NO
Boiler - Capacity	Lit	0
<b>POWERS</b>		
Boiler heater	kW	6
Fan motor	HP	1 ÷ 1,5
<b>CONNECTIONS</b>		
Voltage	230 III / 400V 3N - 50 / 60 Hz	230 III / 400V 3N - 50 -60 Hz
Ø Water inlet	inch	3/8"
Ø Boiler exhaustt	inch	1/2"
Ø Steam inlet	inch	-
Ø Condensate outlet	inch	-
Steam pressure	bar	5
Steam consumption	kg/h	-
Ø Air inlet	inch	1/4"
Ø Air outlet	mm	-
Air pressure	bar	5
Air consumption	Nl/min	40
Sound level	dB	70
<b>DIMENSIONS / WITH PACKING</b>		
Width / Width	mm	1.115 / 1.210
Depth / Depth	mm	630 / 780
Height / Height	mm	1.950 / 2.100
Net weight / Gross weight	kg	119 / 175
Net volume / Gross volume	m <sup>3</sup>	1,37 / 1,99

