



Catalogue :

OTHER REFRIGERATION

Chapter :

REFRIGERATED DISPLAYS

Article :

ERM-150 BOTTLE COOLER 230V 50/60 Hz 1N

Code:

19020901

<u>DIMENSIONS AND WEIGHTS</u>	<u>Net dimensions</u>	<u>Packed</u>
Length	mm	625,00
Depth	mm	520,00
Height	mm	900,00
Weight	kg	51,00
Volume	m3	0,29
<u>ELECTRICITY</u>	230V	50/60Hz
	Power	0,18 kW
Connections	230 V. 1+N+T	2X1,5+T - 4 A
	230 V. III+T	3X10+T - 63 A
	400 V. III+N+T	4X2,5MM2+T
<u>GAS</u>	Not necessary	
<u>WATER</u>	Not necessary	
<u>STEAM</u>	Not necessary	
<u>AIR</u>	Not necessary	
		R-134a
	Refrigeration power	0,166
	Climat class	4
<u>SOUND LEVEL</u>		< 65,00 db
<u>CERTIFICATES</u>	SGS-2103-0906-1	
<u>INSTALLATION - CONNECTIONS</u>	Ø	
	► ELECTRICITY	SI

DESCRIPTION

REFRIGERATED WALL DISPLAYS, ERM-150

SPECIFICATIONS

Sanitary epoxy coated galvanized steel inside.
 Two outside finish options: Either satin stainless steel (Inox version) or black plastic covered galvanized steel (black version).
 40 kg/m3 injected polyurethane isolation.
 Copper piping and aluminium flaps evaporator.
 Hermetically sealed copper serpentine ventilated compressor.
 Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.
 Fitted with a lock.
 Digital display for electronic control of temperature.
 ON/OFF power switch.
 Top horizontal lightning.
 Fitted with two plastic covered steel grid shelves.
 Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Doors: 1
 Capacity: 142 L
 Bottle capacity: 49
 Electric power: 163 W
 Coolant: R-134a
 Dimensions: 625x520x900 mm





Catalogue :
OTHER REFRIGERATION

Chapter :
REFRIGERATED DISPLAYS

Article :
ERM-150 BOTTLE COOLER 230V 50/60 Hz 1N

Code :
19020901

SCHEMA - DIMENSIONS

