



Catalogue :

**OTHER REFRIGERATION**

Chapter :

**REFRIGERATED DISPLAYS**

Article :

**ERM-250 NL BOTTLE COOLER 230V 50/60Hz 1N**

Code:

**19020854**

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	<b>925,00</b>	<b>575,00</b>
Depth	mm	<b>520,00</b>	<b>970,00</b>
Height	mm	<b>900,00</b>	<b>1.025,00</b>
Weight	kg	<b>80,00</b>	<b>83,00</b>
Volume	m3	<b>0,43</b>	<b>0,57</b>
<u>ELECTRICITY</u>		<b>230V</b>	<b>50/60Hz</b>
	Power		<b>0,34 kW</b>
Connections	230 V. 1+N+T	<b>2X1,5+T - 4 A</b>	
	230 V. III+T	<b>3X10+T - 63 A</b>	
	400 V. III+N+T	<b>4X2,5MM2+T</b>	
<u>GAS</u>	Not necessary		
<u>WATER</u>	Not necessary		
<u>STEAM</u>	Not necessary		
<u>AIR</u>	Not necessary		
			<b>R-134a</b>
	Refrigeration power		<b>0,345</b>
	Climat class	<b>4</b>	
<u>SOUND LEVEL</u>			<b>&lt; 65,00 db</b>
<u>CERTIFICATES</u>	<b>SGS-2103-0906-1</b>		
<u>INSTALLATION - CONNECTIONS</u>	<b>Ø</b>		
	► ELECTRICITY		<b>SI</b>

DESCRIPTION

REFRIGERATED WALL DISPLAYS, ERM-250

SPECIFICATIONS

Sanitary epoxy coated galvanized steel inside.  
 Two outside finish options: Either satin stainless steel (Inox version) or black plastic covered galvanized steel (black version).  
 40 kg/m3 injected polyurethane isolation.  
 Copper piping and aluminium flaps evaporator.  
 Hermetically sealed copper serpentine ventilated compressor.  
 Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.  
 Fitted with a lock.  
 Digital display for electronic control of temperature.  
 ON/OFF power switch.  
 Top horizontal lightning.  
 Fitted with two plastic covered steel grid shelves.  
 Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Doors: 2  
 Capacity: 214 L  
 Bottle capacity: 77  
 Electric power: 400 W  
 Coolant: R-134a  
 Dimensions: 925x520x900 mm





Catalogue :  
**OTHER REFRIGERATION**

Chapter :  
**REFRIGERATED DISPLAYS**

Article :  
**ERM-250 NL BOTTLE COOLER 230V 50/60Hz 1N**

Code :  
**19020854**

**SCHEMA - DIMENSIONS**

