



Catalogue :

OTHER REFRIGERATION

Chapter :

REFRIGERATED DISPLAYS

Article :

ERM-350 SS COOLER 230V 50/60Hz 1N

Code:

19038955

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	1.375,00	575,00
Depth	mm	520,00	1.420,00
Height	mm	900,00	1.025,00
Weight	kg	110,00	115,00
Volume	m3	0,64	0,84
<u>ELECTRICITY</u>		230V	50/60Hz
	Power		0,34 kW
Connections	230 V. 1+N+T	2X1,5+T - 4 A	
	230 V. III+T	3 X 2,5 + T - 20A	
	400 V. III+N+T	4X1,5 + T - 16 A	
<u>GAS</u>	Not necessary		
<u>WATER</u>	Not necessary		
<u>STEAM</u>	Not necessary		
<u>AIR</u>	Not necessary		
			R-134a
	Refrigeration power		0,345
	Climat class	4	
<u>SOUND LEVEL</u>			< 65,00 db
<u>INSTALLATION - CONNECTIONS</u>			Ø
	► ELECTRICITY	SI	

DESCRIPTION

REFRIGERATED WALL DISPLAYS, ERM-350 SS

SPECIFICATIONS

Sanitary epoxy coated galvanized steel inside.
 Two outside finish options: Either satin stainless steel (Inox version) or black plastic covered galvanized steel (black version).
 40 kg/m3 injected polyurethane isolation.
 Copper piping and aluminium flaps evaporator.
 Hermetically sealed copper serpentine ventilated compressor.
 Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.
 Fitted with a lock.
 Digital display for electronic control of temperature.
 ON/OFF power switch.
 Top horizontal lightning.
 Fitted with two plastic covered steel grid shelves.
 Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Doors: 3
 Capacity: 327 L
 Bottle capacity: 119
 Electric power: 302 W
 Coolant: R-134a
 Dimensions: 1.375x520x900 mm





Catalogue :
OTHER REFRIGERATION

Chapter :
REFRIGERATED DISPLAYS

Article :
ERM-350 SS COOLER 230V 50/60Hz 1N

Code :
19038955

SCHEMA - DIMENSIONS

