



Catalogue :

**CATERING**

Chapter :

**REFRIGERATION**

Article :

**ERMU-250 BOTTLE COOLER 230V 50/60Hz 1N**

Code:

**19034534**

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	<b>925,00</b>	<b>575,00</b>
Depth	mm	<b>520,00</b>	<b>970,00</b>
Height	mm	<b>800,00</b>	<b>1.025,00</b>
Weight	kg	<b>75,00</b>	<b>78,00</b>
Volume	m3	<b>0,39</b>	<b>0,57</b>

<u>ELECTRICITY</u>		<u>230V</u>	<u>50/60Hz</u>
Power			<b>0,34 kW</b>
Connections	230 V. 1+N+T	<b>2X1,5+T - 4 A</b>	
	230 V. III+T	<b>3X10+T -48 A</b>	
	400 V. III+N+T	<b>4X4+T / 25 A</b>	

GAS Not necessary

WATER Not necessary

STEAM Not necessary

AIR Not necessary

<u>REFRIGERATION</u>		
Gas type - refrigeration		<b>R-134a</b>
Refrigeration power		<b>0,345</b>

Climat class **4**

SOUND LEVEL < **65,00** db

CERTIFICATES **SGS-2103-0906-1**

INSTALLATION - CONNECTIONS **Ø**

► ELECTRICITY **SI**

DESCRIPTION

REFRIGERATED WALL DISPLAYS, ERMU-250

SPECIFICATIONS

Sanitary epoxy coated galvanized steel inside.  
 Outside finish in black plastic covered galvanized steel (black version).  
 40 kg/m3 injected polyurethane isolation.  
 Copper piping and aluminium flaps evaporator.  
 Hermetically sealed copper serpentine ventilated compressor.  
 Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.  
 Fitted with a lock.  
 Digital display for electronic control of temperature.  
 ON/OFF power switch.  
 Top horizontal lightning.  
 Fitted with two plastic covered steel grid shelves.  
 Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Doors: 2  
 Capacity: 214 L  
 Bottle capacity: 77  
 Electric power: 400 W  
 Coolant: R-134a  
 Dimensions: 925x520x800 mm





Catalogue :  
**CATERING**

Chapter :  
**REFRIGERATION**

Article :  
**ERMU-250 BOTTLE COOLER 230V 50/60Hz 1N**

Code :  
**19034534**

**SCHEMA - DIMENSIONS**

