



Catalogue :

CATERING

Chapter :

REFRIGERATION

Article :

ERMU-350 BOTTLE COOLER 230V 50/60Hz1N

Code:

19045196

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	1.375,00	575,00
Depth	mm	520,00	1.420,00
Height	mm	800,00	1.025,00
Weight	kg	103,00	108,00
Volume	m3	0,57	0,84
<u>ELECTRICITY</u>		50/60Hz	
	230V		
	Power		0,34 kW
Connections	230 V. 1+N+T	2X1,5+T - 4 A	
	230 V. III+T	3X4+T - 32 A	
	400 V. III+N+T	4X1,5 +T - 12 A	
<u>GAS</u>	Not necessary		
<u>WATER</u>	Not necessary		
<u>STEAM</u>	Not necessary		
<u>AIR</u>	Not necessary		
<u>REFRIGERATION</u>			
	Gas type - refrigeration		R-134a
	Refrigeration power		0,345
	Climat class	4	
<u>SOUND LEVEL</u>			< 65,00 db
<u>CERTIFICATES</u>	SGS-2103-0906-1		
<u>INSTALLATION - CONNECTIONS</u>			
	► ELECTRICITY		SI

DESCRIPTION

REFRIGERATED WALL DISPLAYS, ERMU-350

SPECIFICATIONS

Sanitary epoxy coated galvanized steel inside.
 Outside finish in black plastic covered galvanized steel (black version).
 40 kg/m3 injected polyurethane isolation.
 Copper piping and aluminium flaps evaporator.
 Hermetically sealed copper serpentine ventilated compressor.
 Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.
 Fitted with a lock.
 Digital display for electronic control of temperature.
 ON/OFF power switch.
 Top horizontal lightning.
 Fitted with two plastic covered steel grid shelves.
 Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Doors: 3
 Capacity: 327 L
 Bottle capacity: 119
 Electric power: 302 W
 Coolant: R-134a
 Dimensions: 1.375x520x800 mm





Catalogue :
CATERING

Chapter :
REFRIGERATION

Article :
ERMU-350 BOTTLE COOLER 230V 50/60Hz1N

Code :
19045196

SCHEMA - DIMENSIONS

