



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-10 M AC

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|-----------------|-----------------|
| Length | mm | 692,00 | 730,00 |
| Depth | mm | 830,00 | 1.000,00 |
| Height | mm | 1.177,00 | 1.410,00 |
| Weigth | Kg | 230,00 | 239,00 |
| Volumen | m3 | 0,68 | 1,03 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|---------------------|
| 230V -1+N | | 2,25 |
| 230V - III | | 2x1,5+T-10 A |
| 400V - III+N | | NO |
| | | NO |

WATER

| | |
|---------------------------|---------------|
| Water consumption (lit/h) | 135,00 |
| Pressure (Kg/cm2) | 2 - 4 |

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) **60,00**

HIGH SPEED WASHER EXTRACTOR, LA-10 M AC

Made of stainless steel.
 Capacity: 10 Kg(1:10).
 Electronic control by microprocessor.
 Set up 16 programs as factory standar with 42 posible variations.
 Four digital display (7 LED segments).
 Phase program indicator by LED in progress.
 Detergent dispenser with 4 compartments(rewash, wash, bleaching and softness).
 Readiness for connection to liquid soap pumps (up to 4).
 Safety door system.
 Drum diameter: 532 mm.
 Deepth drum: 425 mm.
 Door miameter: 290 mm.
 Incorporate speed control for the motor.
 No need to anchorage to the floor.
 Spin speed: 1.000 r.p.m.
 G Factor: 350
 Easy to attach automatic dosser dispenser at rear of machine.
 Water consumption in program n° 2 60°: 135 litres.
 Heating system: Hot water
 Heating element to maintaining: 2 kW.
 Total power: 2,25 kW.
 Dimensions: 692 x 830 x 1.177 mm

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|--------------------|
| ELECTRICITY | 106 | 0 | 871 | | |
| DRAIN | 252 | 0 | 80 | 2" | |
| COLD WATER | 623 | 0 | 1.070 | 3/4" | |
| HOT WATER | 468 | 0 | 1.050 | 3/4" | |

