



### Washer extractors

#### High Spin washer extractors

## HIGH SPEED WASHER EXTRACTOR, LA-10 MP AC

### DIMENSIONS

		Article	Packed
Length	mm	692,00	730,00
Depth	mm	830,00	1.000,00
Height	mm	1.177,00	1.410,00
Weigth	Kg	230,00	239,00
Volumen	m3	0,68	1,03

### ELECTRICITY

Electric power	KW	
230V -1+N		2,25 2x1,5+T-10 A
230V - III		NO
400V - III+N		NO

### WATER

Water consumption (lit/h)	135,00
Pressure (Kg/cm2)	2 - 4

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 60,00

### HIGH SPEED WASHER EXTRACTOR, LA-10 MP AC

Made of stainless steel.

Capacity: 10 Kg(1:10).

Electronic control by microprocessor programmable.

16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...

Digital graphic display to control the washing process and for programming.

Keyboard for the programming and use (4 keys).

PC connection RS-232.

External memory card.

Possibility of external programming or programs transfer.

Detergent dispenser with 4 compartments(prewash, wash, bleaching and softness).

Readiness for connection to liquid soap pumps (up to 7).

Standard user languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian) Option to create another one by the user.

#### WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for every 7 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum rhythm ON-OFF: 1 second.

Safety door system.

Drum diameter: 532 mm.

Depth drum: 425 mm.

Door diameter: 290 mm.

Incorporate speed control for the motor.

No need to anchorage to the floor.

Spin speed: 1.000 r.p.m.

G Factor: 350

Easy to attach automatic doser dispenser at rear of machine.

Water consumption in program n° 2 60°: 135 litres.

Heating system: Hot water

Heating element to maintaining: 2 Kw.

Total power: 2,25 Kw.

Dimensions: 692 x 830 x 1.177 mm

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	106	0	871		0
DRAIN	252	0	80	2"	
SOFT COLD WATER	413	0	1.050	3/4"	
COLD WATER	623	0	1.070	3/4"	
HOT WATER	468	0	1.050	3/4"	

