



Washer extractors

High Spin washer extractors

HIGH SPIN WASHER, LA-120 MP V

DIMENSIONS

		Article	Packed
Length	mm	1.836,00	1.900,00
Depth	mm	1.863,00	1.940,00
Height	mm	2.245,00	2.290,00
Weigth	Kg	3.300,00	3.500,00
Volumen	m3	7,68	8,44

ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		OPC3x10+T-63A
400V - III+N		4x4+T-32A

WATER

Water consumption (lit/h)		1.300,00
Pressure (Kg/cm2)		2 - 4

GAS

Not used

STEAM

Consumption	kg/h	300,00
Pressure	bar	4-8

AIR

Not used

LEVEL SOUND

(dB) 70,00

HIGH SPIN WASHER EXTRACTOR, LA-120 MP V

Softmount machine.

Made of stainless steel.

Capacity: 120 Kg(1:10).

Electronic control by microprocessor programmable.

16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...

Digital grafic display to control the washing process anf for programming.

Keyboard for the programming and use (4 keys).

PC connection RS-232.

External memory card.

Possibility of external programming or programs transfer.

No detergent dispenser.

Readiness for connection to liquid soap pumps (up to 7).

User languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian and Czech).

WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for evey 7 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum thymhm ON-OFF: 1 second.

Safety door system.

Drum diameter: 1.360 mm. Deepth drum: 840 mm.

Door miameter: 700 mm.

Incorporate speed control for the motor.

No need to anchorage to the floor.

Second drain option.

Spin speed: 700 r.p.m. G Factor: 350

Easy to attach automatic dosser dispenser at rear of machine.

Water consumption in program n° 2 60°: 1.300 litres.

Heating system: Steam with pressure 2-4 kg/cm2.

Steam consumption: 60 Kg/cycle (60° program)

Total power: 15 Kw.

Dimensions: 1.836 x 1.863 x 2.245 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	1.400	0	2.250		0
DRAIN	1.100	0	350	4"	
DRAIN	700	0	350	4"	
COLD WATER	730	0	2.105	1-1/2"	
SOFT HOT WATER	450	0	2.105	1-1/2"	
HOT WATER	590	0	2.105	1-1/2"	
STEAM Inlet	1.195	0	2.105	1-1/4"	

