



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-13 M E

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|-----------------|-----------------|
| Length | mm | 790,00 | 830,00 |
| Depth | mm | 870,00 | 1.010,00 |
| Height | mm | 1.321,00 | 1.560,00 |
| Weigth | Kg | 250,00 | 283,00 |
| Volumen | m3 | 0,91 | 1,31 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|-----------------------|
| 230V -1+N | | 9,50 |
| 230V - III | | OPC2x16+T-63A |
| 400V - III+N | | 3x6+T -40 A |
| | | 4x2,5+T - 25 A |

WATER

| | |
|---------------------------|---------------|
| Water consumption (lit/h) | 168,00 |
| Pressure (Kg/cm2) | 2 - 4 |

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) **60,00**

HIGH SPEED WASHER EXTRACTOR, LA-13 M E

Made of stainless steel.
 Capacity: 13 Kg(1:10).
 Electronic control by microprocessor.
 Set up 16 programs as factory standar with 42 possible variations.
 Four digital display (7 LED segments).
 Phase program indicator by LED in progress.
 Detergent dispenser with 4 compartments(prewash, wash, bleaching and softness).
 Readiness for connection to liquid soap pumps (up to 4).
 Safety door system.
 Drum diameter: 620 mm.
 Deepth drum: 430 mm.
 Door miameter: 373 mm.
 Incorporate speed control for the motor.
 No need to anchorage to the floor.
 Spin speed: 1.000 r.p.m.
 G Factor: 350
 Easy to attach automatic dosser dispenser at rear of machine.
 Water consumption in program n° 2 60°: 168 litres.
 Heating system: Electric.
 Elements heating power: 9 Kw.
 Total power: 9,5 Kw.
 Dimensions: 790 x 870 x 1.321 mm.

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|--------------------|
| ELECTRICITY | 108 | 0 | 1.022 | | 0 |
| DRAIN | 269 | 0 | 80 | 2" | |
| COLD WATER | 714 | 0 | 1.216 | 3/4" | |
| HOT WATER | 554 | 0 | 1.196 | 3/4" | |

