



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-13 MP AC

<u>DIMENSIONS</u>		Article	Packed
Length	mm	790,00	830,00
Depth	mm	870,00	1.010,00
Height	mm	1.321,00	1.560,00
Weigth	Kg	250,00	283,00
Volumen	m3	0,91	1,31
<u>ELECTRICITY</u>			
<u>Electric power</u>	KW		3,50
230V -1+N		2x2,5+T-25A	
230V - III			NO
400V - III+N			NO
<u>WATER</u>			
Water consumption (lit/h)			168,00
Pressure (Kg/cm2)			2 - 4
<u>GAS</u>			
Not used			
<u>STEAM</u>		Not used	
<u>AIR</u>		Not used	
<u>LEVEL SOUND</u>		(dB)	60,00

HIGH SPEED WASHER EXTRACTOR, LA-13 MP AC

Made of stainless steel.
Capacity: 13 Kg(1:10).
Electronic control by microprocessor programmable.
16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...
Digital grafic display to control the washing process anf for programming.
Keyboard for the programmation and use (4 keys).
PC connection RS-232.
External memory card.
Possibility of external programmation or programs transfer.
Detergent dispenser with 4 compartments(prewash, wash, bleaching and softness).
Readiness for connection to liquid soap pumps (up to 7).
Standard user languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian) Option to create another one by the user.
WET CLEANING SYSTEM:
-Water levels completely modifiable.
-Possible manual dosing for evey 7 signals during the cycle.
-Minimum washing speed: 15 r.p.m.
-Minimum thythm ON-OFF: 1 second.
Safety door system.
Drum diameter: 620 mm.
Depth drum: 430 mm.
Door miameter: 373 mm.
Incorporate speed control for the motor.
No need to anchorage to the floor.
Second drain option.
Spin speed: 1.000r.p.m.
G Factor: 350
Easy to attach automatic dosser dispenser at rear of machine.
Water consumption in program n° 2 60°: 168 litres.
Heating system: Hot water
Heating element to maintaining: 3 Kw.
Total power: 3,5 Kw.
Dimensions: 790 x 870 x 1.321 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	108	0	1.022		0
DRAIN	269	0	80	2"	
SOFT COLD WATER	494	0	1.196	3/4"	
COLD WATER	714	0	1.216	3/4"	
HOT WATER	554	0	1.196	3/4"	

