



### Washer extractors

#### High Spin washer extractors

## HIGH SPEED WASHER EXTRACTOR, LA-13 MP V

### DIMENSIONS

		Article	Packed
Length	mm	790,00	830,00
Depth	mm	870,00	1.010,00
Height	mm	1.321,00	1.560,00
Weigth	Kg	250,00	283,00
Volumen	m3	0,91	1,31

### ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5+T-10A
230V - III		NO
400V - III+N		NO

### WATER

Water consumption (lit/h)		168,00
Pressure (Kg/cm2)		2 - 4

### GAS

Not used

### STEAM

Consumption	kg/h	35,00
Pressure	bar	2 _ 4

### AIR

Not used

### LEVEL SOUND

(dB) 60,00

### HIGH SPEED WASHER EXTRACTOR, LA-13 MP V

Made of stainless steel.

Capacity: 13 Kg(1:10).

Electronic control by microprocessor programmable.

16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...

Digital grafic display to control the washing process anf for programming.

Keyboard for the programming and use (4 keys).

PC connection RS-232.

External memory card.

Possibility of external programming or programs transfer.

Detergent dispenser with 4 compartments(rewash, wash, bleaching and softness).

Readiness for connection to liquid soap pumps (up to 7).

Standard user languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian) Option to create another one by the user.

#### WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for evey 7 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum thythm ON-OFF: 1 second.

Safety door system.

Drum diameter: 629 mm.

Depth drum: 430 mm.

Door miameter: 373 mm.

Incorporate speed control for the motor.

No need to anchorage to the floor.

Second drain option.

Spin speed: 1.000 r.p.m.

G Factor: 350

Easy to attach automatic dosser dispenser at rear of machine.

Water consumption in program n° 2 60°: 168 litres.

Heating system: Steam with pressure 2-4 kg/cm2.

Total power: 1,5 Kw.

Dimensions: 790 x 870 x 1.321 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	108	0	1.022		0
DRAIN	269	0	80	2"	
SOFT COLD WATER	494	0	1.196	3/4"	
COLD WATER	714	0	1.216	3/4"	
HOT WATER	554	0	1.196	3/4"	
STEAM Inlet	743	0	900	1/2"	

