



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-18 M V

DIMENSIONS

| | | Article | Packed |
|---------|----|----------|----------|
| Length | mm | 885,00 | 930,00 |
| Depth | mm | 914,00 | 1.030,00 |
| Height | mm | 1.428,00 | 1.550,00 |
| Weigth | Kg | 360,00 | 393,00 |
| Volumen | m3 | 1,16 | 1,61 |

ELECTRICITY

| Electric power | KW | |
|----------------|----|------------------------|
| 230V -1+N | | 2,20 2x1,5+T - 16 A |
| 230V - III | | NO |
| 400V - III+N | | NO |

WATER

| | | |
|---------------------------|--|--------|
| Water consumption (lit/h) | | 218,00 |
| Pressure (Kg/cm2) | | 2 - 4 |

GAS

Not used

STEAM

| | | |
|-------------|------|-------|
| Consumption | kg/h | 50,00 |
| Pressure | bar | 2_4 |

AIR

Not used

LEVEL SOUND

(dB) 60,00

HIGH SPEED WASHER EXTRACTOR, LA-18 M V

Made of stainless steel.
Capacity: 18 Kg(1:10).
Electronic control by microprocessor.
Set up 16 programs as factory standar with 42 posible variations.
Four digital display (7 LED segments).
Phase program indicator by LED in progress.
Detergent dispenser with 4 compartments(rewash, wash, bleaching and softness).
Readiness for connection to liquid soap pumps (up to 4).
Safety door system.
Drum diameter: 700 mm.
Deepest drum: 470 mm.
Door miameter: 373 mm.
Incorporate speed control for the motor.
No need to anchorage to the floor.
Spin speed: 950 r.p.m.
G Factor: 350
Easy to attach automatic dosser dispenser at rear of machine.
Water consumption in program n° 2 60°: 218 litres.
Heating system: Steam with pressure 2-4 kg/cm2.
Total power: 2,2 Kw.
Dimensions: 885 x 914 x 1.428 mm.

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-----|---|-------|----------|-------------|
| ELECTRICITY | 109 | 0 | 1.129 | | 0 |
| DRAIN | 347 | 0 | 80 | 2" | |
| COLD WATER | 815 | 0 | 1.320 | 3/4" | |
| HOT WATER | 660 | 0 | 1.300 | 3/4" | |
| STEAM Inlet | 839 | 0 | 1.004 | 1/2" | |

