



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-18 MP E

<u>DIMENSIONS</u>		Article	Packed
Length	mm	885,00	930,00
Depth	mm	914,00	1.030,00
Height	mm	1.428,00	1.550,00
Weigth	Kg	360,00	393,00
Volumen	m3	1,16	1,61
<u>ELECTRICITY</u>			
<u>Electric power</u>	KW		12,75
230V -1+N		OPC2x25+T-100A	
230V - III		3x10+T -63 A	
400V - III+N		4x4+T - 32 A	
<u>WATER</u>			
Water consumption (lit/h)			0,00
Pressure (Kg/cm2)			2 - 4
<u>GAS</u>			
Not used			
<u>STEAM</u>		Not used	
<u>AIR</u>		Not used	
<u>LEVEL SOUND</u>		(dB)	60,00

HIGH SPEED WASHER EXTRACTOR, LA-18 MP E

Made of stainless steel.

Capacity: 18 Kg(1:10).

Electronic control by microprocessor programmable.

16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...

Digital grafic display to control the washing process anf for programming.

Keyboard for the programming and use (4 keys).

PC connection RS-232.

External memory card.

Possibility of external programming or programs transfer.

Detergent dispenser with 4 compartments(prewash, wash, bleaching and softness).

Readiness for connection to liquid soap pumps (up to 7).

Standard user languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian) Option to create another one by the user.

WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for evey 7 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum thythm ON-OFF: 1 second.

Safety door system.

Drum diameter: 700 mm.

Depth drum: 470 mm.

Door miameter: 373 mm.

Incorporate speed control for the motor.

No need to anchorage to the floor.

Second drain option.

Spin speed: 950 r.p.m.

G Factor: 350

Easy to attach automatic dosser dispenser at rear of machine.

Water consumption in program n° 2 60°: 218 litres.

Heating system: Electric.

Elements heating power: 12 Kw.

Total power: 12,75 Kw.

Dimensions: 885 x 914 x 1.428 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
HOT WATER	660	0	1.300	3/4"	
DRAIN	347	0	80	2"	
SOFT COLD WATER	606	0	1.300	3/4"	
COLD WATER	815	0	1.320	3/4"	

