



**Washer extractors**

**High Spin washer extractors**

**HIGH SPEED WASHER EXTRACTOR, LA-25 M AC**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>980,00</b>	<b>1.040,00</b>
Depth	mm	<b>1.041,00</b>	<b>1.160,00</b>
Height	mm	<b>1.598,00</b>	<b>1.700,00</b>
Weigth	Kg	<b>490,00</b>	<b>545,00</b>
Volumen	m3	<b>1,63</b>	<b>2,05</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V -1+N		<b>2x10+T - 50 A</b>
230V - III		<b>OPC3x4+T - 32 A</b>
400V - III+N		<b>4x1,5+T-16A</b>

**WATER**

Water consumption (lit/h)	<b>336,00</b>
Pressure (Kg/cm2)	<b>2 - 4</b>

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

**LEVEL SOUND**

(dB) **60,00**

**HIGH SPEED WASHER EXTRACTOR, LA-25 M AC**

Made of stainless steel.  
 Capacity: 25 Kg(1:10).  
 Electronic control by microprocessor.  
 Set up 16 programs as factory standar with 42 possible variations.  
 Four digital display (7 LED segments).  
 Phase program indicator by LED in progress.  
 Detergent dispenser with 4 compartments(rewash, wash, bleaching and softness).  
 Readiness for connection to liquid soap pumps (up to 4).  
 Safety door system.  
 Drum diameter: 770 mm.  
 Deepth drum: 530 mm.  
 Door miameter: 373 mm.  
 Incorporate speed control for the motor.  
 No need to anchorage to the floor.  
 Spin speed: 900 r.p.m.  
 G Factor: 350  
 Easy to attach automatic dosser dispenser at rear of machine.  
 Water consumption in program n° 2 60°: 336 litres.  
 Heating system: Hot water  
 Heating element to maintaining: 6 Kw.  
 Total power: 7 Kw.  
 Dimensions: 980 x 1.041 x 1.598 mm.

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	

