



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-25 M E

<u>DIMENSIONS</u>		Article	Packed
Length	mm	980,00	1.040,00
Depth	mm	1.041,00	1.160,00
Height	mm	1.598,00	1.700,00
Weigth	Kg	490,00	545,00
Volumen	m3	1,63	2,05

<u>ELECTRICITY</u>		Article	Packed
<u>Electric power</u>	KW		19,00
230V -1+N			NO
230V - III		OPC3x16+T-80A	
400V - III+N		4x6+T-50A	

<u>WATER</u>		Packed
Water consumption (lit/h)		336,00
Pressure (Kg/cm2)		2 - 4

GAS
Not used

STEAM Not used

AIR Not used

<u>LEVEL SOUND</u>	(dB)	Packed
		60,00

HIGH SPEED WASHER EXTRACTOR, LA-25 M E

Made of stainless steel.
Capacity: 25 Kg(1:10).
Electronic control by microprocessor.
Set up 16 programs as factory standar with 42 possible variations.
Four digital display (7 LED segments).
Phase program indicator by LED in progress.
Detergent dispenser with 4 compartments(rewash, wash, bleaching and softness).
Readiness for connection to liquid soap pumps (up to 4).
Safety door system.
Drum diameter: 770 mm.
Depth drum: 530 mm.
Door diameter: 373 mm.
Incorporate speed control for the motor.
No need to anchorage to the floor.
Spin speed: 900 r.p.m.
G Factor: 350
Easy to attach automatic doser dispenser at rear of machine.
Water consumption in program n° 2 60°: 336 litres.
Heating system: Electric.
Elements heating power: 18 Kw.
Total power: 19 Kw.
Dimensions: 980 x 1.041 x 1.598 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	

