



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-25 M V

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	980,00	1.040,00
Depth	mm	1.041,00	1.160,00
Height	mm	1.598,00	1.700,00
Weigth	Kg	490,00	545,00
Volumen	m3	1,63	2,05

ELECTRICITY

<u>Electric power</u>	KW		3,00
230V -1+N		2x1,5+T - 16 A	
230V - III		OPC3x1,5+T - 10 A	
400V - III+N		4x1,5+T-6A	

WATER

Water consumption (lit/h)			336,00
Pressure (Kg/cm2)			2 - 4

GAS

Not used

STEAM

Consumption	kg/h		75,00
Pressure	bar		

AIR

Not used

LEVEL SOUND

	(dB)		60,00
--	------	--	--------------

HIGH SPEED WASHER EXTRACTOR, LA-25 M V

Made of stainless steel.
Capacity: 25 Kg(1:10).
Electronic control by microprocessor.
Set up 16 programs as factory standar with 42 possible variations.
Four digital display (7 LED segments).
Phase program indicator by LED in progress.
Detergent dispenser with 4 compartments(rewash, wash, bleaching and softness).
Readiness for connection to liquid soap pumps (up to 4).
Safety door system.
Drum diameter: 770 mm.
Depth drum: 530 mm.
Door miameter: 373 mm.
Incorporate speed control for the motor.
No need to anchorage to the floor.
Spin speed: 900 r.p.m.
G Factor: 350
Easy to attach automatic dosser dispenser at rear of machine.
Water consumption in program n° 2 60°: 336 litres.
Heating system: Steam with pressure 2-4 kg/cm2.
Total power: 3 Kw.
Dimensions: 980 x 1.041 x 1.598 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	
STEAM Inlet	840	0	1.010	3/4"	

