



### Washer extractors

#### High Spin washer extractors

## HIGH SPEED WASHER EXTRACTOR, LA-25 MP AC

<u>DIMENSIONS</u>		Article	Packed
Length	mm	980,00	1.040,00
Depth	mm	1.041,00	1.160,00
Height	mm	1.598,00	1.700,00
Weigth	Kg	490,00	545,00
Volumen	m3	1,63	2,05
<u>ELECTRICITY</u>			
<u>Electric power</u>	KW		7,00
230V -1+N		2x10+T - 50 A	
230V - III		OPC3x4+T - 32 A	
400V - III+N		4x1,5+T-16A	
<u>WATER</u>			
Water consumption (lit/h)			336,00
Pressure (Kg/cm2)			2 - 4
<u>GAS</u>			
Not used			
<u>STEAM</u>		Not used	
<u>AIR</u>		Not used	
<u>LEVEL SOUND</u>		(dB)	60,00

### HIGH SPEED WASHER EXTRACTOR, LA-25 MP AC

Made of stainless steel.  
Capacity: 25 Kg(1:10).  
Electronic control by microprocessor programmable.  
16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...  
Digital grafic display to control the washing process anf for programming.  
Keyboard for the programmation and use (4 keys).  
PC connection RS-232.  
External memory card.  
Possibility of external programmation or programs transfer.  
Detergent dispenser with 4 compartments(prewash, wash, bleaching and softness).  
Readiness for connection to liquid soap pumps (up to 7).  
Standard user languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian) Option to create another one by the user.  
**WET CLEANING SYSTEM:**  
-Water levels completely modifiable.  
-Possible manual dosing for evey 7 signals during the cycle.  
-Minimum washing speed: 15 r.p.m.  
-Minimum thythm ON-OFF: 1 second.  
Safety door system.  
Drum diameter: 770 mm.  
Depth drum: 530 mm.  
Door miameter: 373 mm.  
Incorporate speed control for the motor.  
No need to anchorage to the floor.  
Second drain option.  
Spin speed: 900 r.p.m.  
G Factor: 350  
Easy to attach automatic dosser dispenser at rear of machine.  
Water consumption in program n° 2 60°: 336 litres.  
Heating system: Hot water  
Heating element to maintaining: 6 Kw.  
Total power: 7 Kw.  
Dimensions: 980 x 1.041 x 1.598 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
SOFT COLD WATER	606	0	1.300	3/4"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	

