



Washer extractors

High Spin washer extractors

HIGH SPEED WASHER EXTRACTOR, LA-25 MP V

DIMENSIONS

		Article	Packed
Length	mm	980,00	1.040,00
Depth	mm	1.041,00	1.160,00
Height	mm	1.598,00	1.700,00
Weigth	Kg	490,00	545,00
Volumen	m3	1,63	2,05

ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5+T - 16 A
230V - III		OPC3X1,5+T- 10A
400V - III+N		4x1,5+T-6A

WATER

Water consumption (lit/h)		336,00
Pressure (Kg/cm2)		2 - 4

GAS

Not used

STEAM

Consumption	kg/h	75,00
Pressure	bar	

AIR

Not used

LEVEL SOUND

(dB) 60,00

HIGH SPEED WASHER EXTRACTOR, LA-25 MP V

Made of stainless steel.

Capacity: 25 Kg(1:10).

Electronic control by microprocessor programmable.

16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...

Digital grafic display to control the washing process anf for programming.

Keyboard for the programming and use (4 keys).

PC connection RS-232.

External memory card.

Possibility of external programming or programs transfer.

Detergent dispenser with 4 compartments(prewash, wash, bleaching and softness).

Readiness for connection to liquid soap pumps (up to 7).

Standard user languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian) Option to create another one by the user.

WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for evey 7 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum thrythm ON-OFF: 1 second.

Safety door system.

Drum diameter: 770 mm.

Depth drum: 530 mm.

Door miameter: 373 mm.

Incorporate speed control for the motor.

No need to anchorage to the floor.

Second drain option.

Spin speed: 900 r.p.m.

G Factor: 350

Easy to attach automatic dosser dispenser at rear of machine.

Water consumption in program n° 2 60°: 336 litres.

Heating system: Steam with pressure 2-4 kg/cm2.

Total power: 3 Kw.

Dimensions: 980 x 1.041 x 1.598 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		
DRAIN	347	0	80		
SOFT COLD WATER	606	0	1.300	3/4"	
COLD WATER	815	0	1.320	3/4"	
SOFT HOT WATER	660	0	1.300	3/4"	
STEAM Inlet	840	0	1.010	3/4"	

