



Washer extractors

High Spin washer extractors

HIGH SPIN WASHER, LA-40 MP AC

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|-----------------|-----------------|
| Length | mm | 1.478,00 | 1.540,00 |
| Depth | mm | 1.394,00 | 1.480,00 |
| Height | mm | 1.905,00 | 1.970,00 |
| Weigth | Kg | 1.350,00 | 1.450,00 |
| Volumen | m3 | 3,92 | 4,49 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|----------------------|
| 230V -1+N | | 12,10 |
| 230V - III | | NO |
| 400V - III+N | | OPC3x10+T-63A |
| | | 4x4+T-32A |

WATER

| | |
|---------------------------|---------------|
| Water consumption (lit/h) | 420,00 |
| Pressure (Kg/cm2) | 2 - 4 |

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) **70,00**

HIGH SPIN WASHER EXTRACTOR, LA-40 MP AC

Softmount machine.
 Made of stainless steel.
 Capacity: 40 Kg(1:10).
 Electronic control by microprocessor programmable.
 16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...
 Digital grafic display to control the washing process anf for programming.
 Keyboard for the programming and use (4 keys).
 PC connection RS-232.
 External memory card.
 Possibility of external programming or programs transfer.
 Detergent dispenser with 5 compartments(prewash, wash, bleaching and softness).
 Readiness for connection to liquid soap pumps (up to 7).
 User languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian and Czech).
WET CLEANING SYSTEM:
 -Water levels completely modifiable.
 -Possible manual dosing for evey 7 signals during the cycle.
 -Minimum washing speed: 15 r.p.m.
 -Minimum thyrhm ON-OFF: 1 second.
 Safety door system.
 Drum diameter: 918 mm. Depth drum: 594 mm.
 Door miameter: 560 mm.
 Incorporate speed control for the motor.
 No need to anchorage to the floor.
 Second drain option.
 Spin speed: 850 r.p.m. G Factor: 350
 Easy to attach automatic dosser dispenser at rear of machine.
 Water consumption in program n° 2 60°: 420 litres.
 Heating system: Hot water
 Heating element to maintaining: 9 kW.
 Total power: 12,1 Kw.
 Dimensions: 1.478 x 1.394 x 1.905 mm.

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|--------------------|
| ELECTRICITY | 770 | 0 | 1.650 | | 0 |
| DRAIN | 765 | 0 | 410 | 3" | |
| DRAIN | 545 | 0 | 410 | 3" | |
| COLD WATER | 735 | 0 | 1.515 | 1" | |
| SOFT HOT WATER | 435 | 0 | 1.515 | 1" | |
| HOT WATER | 585 | 0 | 1.515 | 1" | |

