



### Washer extractors

#### High Spin washer extractors

## HIGH SPIN WASHER, LA-40 MP E

### DIMENSIONS

		Article	Packed
Length	mm	1.478,00	1.540,00
Depth	mm	1.394,00	1.480,00
Height	mm	1.905,00	1.970,00
Weigth	Kg	1.300,00	1.450,00
Volumen	m3	3,92	4,49

### ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		3x25+T-80A
400V - III+N		4x10+T-50A

### WATER

Water consumption (lit/h)	420,00
Pressure (Kg/cm2)	2 - 4

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 70,00

### HIGH SPIN WASHER EXTRACTOR, LA-40 MP E

Softmount machine.

Made of stainless steel.

Capacity: 40 Kg(1:10).

Electronic control by microprocessor programmable.

16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...

Digital graphic display to control the washing process and for programming.

Keyboard for the programming and use (4 keys).

PC connection RS-232.

External memory card.

Possibility of external programming or programs transfer.

Detergent dispenser with 5 compartments(pretwash, wash, bleaching and softness).

Readiness for connection to liquid soap pumps (up to 7).

User languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian and Czech).

#### WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for every 7 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum rhythm ON-OFF: 1 second.

Safety door system.

Drum diameter: 918 mm. Depth drum: 594 mm.

Door diameter: 560 mm.

Incorporate speed control for the motor.

No need to anchorage to the floor.

Second drain option.

Spin speed: 850 r.p.m. G Factor: 350

Easy to attach automatic doser dispenser at rear of machine.

Water consumption in program nº 2 60°: 420 litres.

Heating system: Electric.

Elements heating power: 24 Kw.

Total power: 31,3 Kw.

Dimensions: 1.478 x 1.394 x 1.905 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	770	0	1.650		0
DRAIN	765	0	410	3"	
DRAIN	545	0	410	3"	
COLD WATER	735	0	1.515	1"	
SOFT HOT WATER	435	0	1.515	1"	
HOT WATER	585	0	1.515	1"	

