



Washer extractors

High Spin washer extractors

HIGH SPIN WASHER, LA-40 MP V

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.478,00	1.540,00
Depth	mm	1.394,00	1.480,00
Height	mm	1.905,00	1.970,00
Weigth	Kg	1.350,00	1.450,00
Volumen	m3	3,92	4,49

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		7,50
230V - III		NO
400V - III+N		OPC3x4+T-32A
		4x1,5+T-16A

WATER

Water consumption (lit/h)		420,00
Pressure (Kg/cm2)		2 - 4

GAS

Not used

STEAM

Consumption	kg/h	100,00
Pressure	bar	2-4

AIR

Not used

LEVEL SOUND

(dB) **70,00**

HIGH SPIN WASHER EXTRACTOR, LA-40 MP V

Softmount machine.
 Made of stainless steel.
 Capacity: 40 Kg(1:10).
 Electronic control by microprocessor programmable.
 16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...
 Digital grafic display to control the washing process anf for programming.
 Keyboard for the programming and use (4 keys).
 PC connection RS-232.
 External memory card.
 Possibility of external programming or programs transfer.
 Detergent dispenser with 5 compartments(rewash, wash, bleaching and softness).
 Readiness for connection to liquid soap pumps (up to 7).
 User languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian and Czech).
WET CLEANING SYSTEM:
 -Water levels completely modifiable.
 -Possible manual dosing for evey 7 signals during the cycle.
 -Minimum washing speed: 15 r.p.m.
 -Minimum thrythm ON-OFF: 1 second.
 Safety door system.
 Drum diameter: 918 mm. Depth drum: 594 mm.
 Door miameter: 560 mm.
 Incorporate speed control for the motor.
 No need to anchorage to the floor.
 Second drain option.
 Spin speed: 850 r.p.m. G Factor: 350
 Easy to attach automatic dosser dispenser at rear of machine.
 Water consumption in program n° 2 60°: 420 litres.
 Heating system: Steam with pressure 2-4 kg/cm2.
 Steam consumption: 22 Kg/cycle (60° program)
 Total power: 7,5 Kw.
 Dimensions: 1.478 x 1.394 x 1.905 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	770	0	1.650		0
DRAIN	545	0	410	3"	
DRAIN	765	0	410	3"	
COLD WATER	735	0	1.515	1"	
SOFT HOT WATER	435	0	1.515	1"	
HOT WATER	585	0	1.515	1"	
STEAM Inlet	880	0	1.515	3/4"	

