



**Washer extractors**

**High Spin washer extractors**

**HIGH SPIN WASHER, LA-60 MP AC**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>1.478,00</b>	<b>1.540,00</b>
Depth	mm	<b>1.444,00</b>	<b>1.580,00</b>
Height	mm	<b>1.905,00</b>	<b>1.970,00</b>
Weigth	Kg	<b>1.600,00</b>	<b>1.700,00</b>
Volumen	m3	<b>4,07</b>	<b>4,79</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V -1+N		<b>NO</b>
230V - III		<b>OPC3x16+T-80A</b>
400V - III+N		<b>4x6+T-50A</b>

**WATER**

Water consumption (lit/h)	<b>650,00</b>
Pressure (Kg/cm2)	<b>2 - 4</b>

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

**LEVEL SOUND**

(dB) **70,00**

**HIGH SPIN WASHER EXTRACTOR, LA-60 MP AC**

Softmount machine.  
 Made of stainless steel.  
 Capacity: 60 Kg(1:10).  
 Electronic control by microprocessor programmable.  
 16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...  
 Digital grafic display to control the washing process anf for programming.  
 Keyboard for the programming and use (4 keys).  
 PC connection RS-232.  
 External memory card.  
 Possibility of external programming or programs transfer.  
 Detergent dispenser with 5 compartments(rewash, wash, bleaching and softness).  
 Readiness for connection to liquid soap pumps (up to 7).  
 User languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian and Czech).  
**WET CLEANING SYSTEM:**  
 -Water levels completely modifiable.  
 -Possible manual dosing for evey 7 signals during the cycle.  
 -Minimum washing speed: 15 r.p.m.  
 -Minimum thrythm ON-OFF: 1 second.  
 Safety door system.  
 Drum diameter: 1.048 mm. Deepth drum: 684 mm.  
 Door miameter: 560 mm.  
 Incorporate speed control for the motor.  
 No need to anchorage to the floor.  
 Second drain option.  
 Spin speed: 760 r.p.m. G Factor: 350  
 Easy to attach automatic dosser dispenser at rear of machine.  
 Water consumption in program n° 2 60°: 650 litres.  
 Heating system: Hot water  
 Heating element to maintaining: 12 KW.  
 Total power: 16 KW.  
 Dimensions: 1.478 x 1.444 x 1.905 mm.

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	770	0	1.515		0
DRAIN	545	0	410	3"	
DRAIN	765	0	410	3"	
COLD WATER	735	0	1.665	1"	
SOFT HOT WATER	435	0	1.665	1"	
HOT WATER	585	0	1.665	1"	

