



Washer extractors

High Spin washer extractors

HIGH SPIN WASHER, LA-60 MP V

DIMENSIONS

		Article	Packed
Length	mm	1.478,00	1.540,00
Depth	mm	1.444,00	1.580,00
Height	mm	1.905,00	1.970,00
Weigth	Kg	1.600,00	1.700,00
Volumen	m3	4,07	4,79

ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		OPC3x6+T-40A
400V - III+N		4x2,5+T-25A

WATER

Water consumption (lit/h)		650,00
Pressure (Kg/cm2)		2 - 4

GAS

Not used

STEAM

Consumption	kg/h	150,00
Pressure	bar	2-4

AIR

Not used

LEVEL SOUND

(dB) 70,00

HIGH SPIN WASHER EXTRACTOR, LA-60 MP V

Softmount machine.
 Made of stainless steel.
 Capacity: 60 Kg(1:10).
 Electronic control by microprocessor programmable.
 16 standard washing programs and possibility to create 84 new programs with all the characteristics: temperature, time, speed...
 Digital grafic display to control the washing process anf for programming.
 Keyboard for the programming and use (4 keys).
 PC connection RS-232.
 External memory card.
 Possibility of external programming or programs transfer.
 Detergent dispenser with 5 compartments(rewash, wash, bleaching and softness).
 Readiness for connection to liquid soap pumps (up to 7).
 User languages: (Spanish, English, French, Italian, German, Portuguese, Turkish, Polish, Russian and Czech).
WET CLEANING SYSTEM:
 -Water levels completely modifiable.
 -Possible manual dosing for evey 7 signals during the cycle.
 -Minimum washing speed: 15 r.p.m.
 -Minimum thrythm ON-OFF: 1 second.
 Safety door system.
 Drum diameter: 1.048 mm. Deepth drum: 684 mm.
 Door miameter: 560 mm.
 Incorporate speed control for the motor.
 No need to anchorage to the floor.
 Second drain option.
 Spin speed: 760 r.p.m. G Factor: 350
 Easy to attach automatic dosser dispenser at rear of machine.
 Water consumption in program n° 2 60°: 650 litres.
 Heating system: Steam with pressure 2-4 kg/cm2.
 Steam consumption: 30 Kg/cycle (60° program)
 Total power: 11 Kw.
 Dimensions: 1.478 x 1.444 x 1.905 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	770	0	1.515		0
DRAIN	765	0	410	3"	
DRAIN	545	0	410	3"	
COLD WATER	735	0	1.515	1"	
SOFT HOT WATER	435	0	1.515	1"	
HOT WATER	585	0	1.515	1"	
STEAM Inlet	940	0	1.665	3/4"	

