



Laundry for Self-Service

Semi industrial high Spin washer extractors

## HIGH SPIN WASHER EXTRACTOR, LA-8 MA E

### DIMENSIONS

		Article	Packed
Length	mm	683,00	700,00
Depth	mm	711,00	730,00
Height	mm	1.092,00	1.300,00
Weigth	Kg	113,00	123,00
Volumen	m3	0,53	0,67

### ELECTRICITY

Electric power	KW	
230V -1+N		10,70
		2x4+T-32A
230V - III		3x2,5+T -20A
400V - III+N		4x1,5+T -16A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### HIGH SPIN WASHER EXTRACTOR, LA-8 MA E

External case made in white varnished steel.

With electronic coin / token meter incorporated in each machine.

Stainless steel wash basket and outer tub.

Four shock suspension.

Capacity: 8 Kg.

Electronic programmable controls.

Cycles: Normal, Permanent press or delicate.

Water temperatures: 40°C - 60°C - 90°C - Permanent Press / 60°C -

Delicate / 30°C

Cycle time: 31 - 35 minutes.

Basket volume: 80 litres.

Spin speed: 500 - 650 - 1.000 rpm.

Motor with variable speed induction, 750 W (3/4 HP) and thermal protection.

Heating elements: 4,8 KW.

Maximun power: 5,55 KW.

Dimensions; 683 x 711 x 1.092 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	895		0
HOT WATER	100	0	740	3/4"	
COLD WATER	100	0	780	3/4"	
DRAIN	110	0	90	25 mm	

