



Washer extractors

L MED Sanitary barrier washer extractors

SANITARY BARRIER WASHER EXTRACTOR, L MED/E-22 MPP

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.180,00	1.324,00
Depth	mm	910,00	1.094,00
Height	mm	1.385,00	1.504,00
Weigth	Kg	450,00	473,00
Volumen	m3	1,49	2,18

ELECTRICITY

<u>Electric power</u>		KW	20,20
230V -1+N			NO
230V - III		OPC3x16+T-80A	
400V - III+N			4x6+T-50A

WATER

Water consumption (lit/h)			198,00
Pressure (Kg/cm2)			2 - 6

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) **65,00**

SANITARY BARRIER WASHER EXTRACTOR, L MED/E-22 MPP

Made of stainless steel.
 Load Capacity : 22 kg. (Rate 1:10)
 Inner and outer drums ,doors and external panels in stainless steel.
 High speed Sanitary Barrier washer extractor with two opposed doors.
 One door at each side.
 Sanitary system that avoid mixed the dirty and clean cloths.
 Microprocessor control that allow to have fixed 5 programs and the possibility to choose another 25 that afford to select temperature , time and phase of washing.
 Display indicator the phase of program .
 Push button to advance the program.
 Electronic thermostat.
 Detergent container with 4 compartments (Pre-wash, wash, bleachers and softeners).
 Safety switch for door opening.
 Horizontal rotation with two compartments.
 Drum diameter : 633 mm.
 Depth drum : 700 mm.
 Volume: 220 litres.
 Door dimensions : 400x315 mm.
 Motor with frequency variation incorporated.
 Speed : 1.000 tpm.
 G factor : 361
 Prepared for connecting liquid additives.
 Heating by electricity.
 Heating power: 18 KW
 Electric connection : 400 V +N+T.
 Maximum power : 20,2 KW.
 Need to anchorage to the floor.
 Dimensions : 1.180 x 910 x 1.385 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	980	405	1.240		
DRAIN	980	350	140	50 mm	
SOFT COLD WATER	980	210	1.155	3/4"	
COLD WATER	980	210	1.255	3/4"	
HOT WATER	980	425	1.155	3/4"	

