



**Washer extractors**

**Normal Spin washer extractors**

**NORMAL SPIN WASHER EXTRACTOR,  
LN-10 M E**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>719,00</b>	<b>760,00</b>
Depth	mm	<b>738,00</b>	<b>1.010,00</b>
Height	mm	<b>1.177,00</b>	<b>1.410,00</b>
Weigth	Kg	<b>217,00</b>	<b>225,00</b>
Volumen	m3	<b>0,62</b>	<b>1,08</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V - I+N		<b>2x10+T-50A</b>
230V - III		<b>3x4+T-32A</b>
400V - III+N		<b>4x1,5+T-16A</b>

**WATER**

Water consumption (lit/h)	<b>135,00</b>
Pressure (Kg/cm2)	<b>2 - 4</b>

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

**LEVEL SOUND**

(dB) **60,00**

**NORMAL SPIN WASHER EXTRACTOR, LN-10 M E**

Hardmount machine.  
 Elements not included.  
 Machine must be fixed to the floor.  
 Stainless steel construction.  
 Capacity: 10 Kg(1:10).  
 Integrated standard microprocessor  
 16 standard washing programs.  
 Any of them can be selected as the standard one.  
 Configurable water levels +10 % ÷ - 10%.  
 It is possible to configure the times and temperatures of each phase, as well as to cancel them.  
 Phase monitoring thanks to 8 LED indicators.  
 7-segment display with 4 digits.  
 Up to 4 dosage signals.  
 Possibility to install one automatic detergent doser on the rear of the machine.  
 Detergent deposit with 4 compartments (pre-wash, wash, bleachers and softeners).  
 Safety switch for door opening.  
 Motor with frequency variator incorporated.  
 Drum diameter: 620 mm.  
 Drum depth: 330 mm.  
 Door diameter: 373 mm.  
 Spin speed: 538 r.p.m.  
 G Factor: 100.  
 WRAS approved product.  
 ETL certified product.  
 Heating system: Electric.  
 Heating power: 6 kW.  
 Total power: 6,25 kW.  
 Dimensions: 719 x 738 x 1.177 mm.

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	106	0	871		0
DRAIN	252	0	80	3"	
COLD WATER	623	0	1.070	3/4"	
HOT WATER	468	0	1.050	3/4"	

