



Washer extractors

Normal Spin washer extractors

NORMAL SPIN WASHER EXTRACTOR, LN-25 M AC

DIMENSIONS

		Article	Packed
Length	mm	885,00	930,00
Depth	mm	1.036,00	1.160,00
Height	mm	1.321,00	1.560,00
Weigth	Kg	340,00	370,00
Volumen	m3	1,21	1,68

ELECTRICITY

Electric power	KW	
230V -1+N		2,20
230V - III		2x1,5+T-16A
400V - III+N		

WATER

Water consumption (lit/h)		336,00
Pressure (Kg/cm2)		2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 60,00

NORMAL SPIN WASHER EXTRACTOR, LN-25 M AC

Hardmount machine.
Elements not included.
Machine must be fixed to the floor.
Stainless steel construction.
Capacity: 25 Kg(1:10).
Integrated standard microprocessor
16 standard washing programs.
Any of them can be selected as the standard one.
Configurable water levels +10 % ÷ - 10%.
It is possible to configure the times and temperatures of each phase, as well as to cancel them.
Phase monitoring thanks to 8 LED indicators.
7-segment display with 4 digits.
Up to 4 dosage signals.
Possibility to install one automatic detergent doser on the rear of the machine.
Detergent deposit with 4 compartments (pre-wash, wash, bleachers and softeners).
Safety switch for door opening.
Motor with frequency variator incorporated.
Drum diameter: 770 mm.
Drum depth: 530 mm.
Door diameter: 373 mm.
Spin speed: 483 r.p.m.
G Factor: 100.
WRAS approved product.
ETL certified product.
Heating system: Hot water.
Total electric power: 2,20 kW.
Dimensions: 885 x 1.036 x 1.321 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	

