



**Washer extractors**

**Normal Spin washer extractors**

**NORMAL SPIN WASHER EXTRACTOR,  
LN-35 M AC**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>979,00</b>	<b>1.020,00</b>
Depth	mm	<b>1.166,00</b>	<b>1.240,00</b>
Height	mm	<b>1.428,00</b>	<b>1.680,00</b>
Weigth	Kg	<b>473,00</b>	<b>503,00</b>
Volumen	m3	<b>1,63</b>	<b>2,12</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V -1+N		<b>2x1,5+T - 16 A</b>
230V - III		
400V - III+N		

**WATER**

Water consumption (lit/h)		<b>336,00</b>
Pressure (Kg/cm2)		<b>2 - 4</b>

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

**LEVEL SOUND**

(dB) **60,00**

**NORMAL SPIN WASHER EXTRACTOR, LN-35 M AC**

Hardmount machine.  
 Elements not included.  
 Machine must be fixed to the floor.  
 Stainless steel construction.  
 Capacity: 35 Kg(1:10).  
 Integrated standard microprocessor  
 16 standard washing programs.  
 Any of them can be selected as the standard one.  
 Configurable water levels +10 % ÷ - 10%.  
 It is possible to configure the times and temperatures of each phase, as well as to cancel them.  
 Phase monitoring thanks to 8 LED indicators.  
 7-segment display with 4 digits.  
 Up to 4 dosage signals.  
 Possibility to install one automatic detergent doser on the rear of the machine.  
 Detergent deposit with 4 compartments (pre-wash, wash, bleachers and softeners).  
 Safety switch for door opening.  
 Motor with frequency variator incorporated.  
 Drum diameter: 860 mm.  
 Drum depth: 602 mm.  
 Door diameter: 560 mm.  
 Spin speed: 458 r.p.m.  
 G Factor: 100.  
 WRAS approved product.  
 ETL certified product.  
 Heating system: Hot water.  
 Total electric power: 3,00 kW.  
 Dimensions: 979 x 1.166 x 1.428 mm.

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	

