



Washer extractors

Normal Spin washer extractors

**NORMAL SPIN WASHER EXTRACTOR,
LN-35 M E**

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	979,00	1.020,00
Depth	mm	1.166,00	1.240,00
Height	mm	1.428,00	1.680,00
Weigth	Kg	473,00	503,00
Volumen	m3	1,63	2,12

ELECTRICITY

<u>Electric power</u>		KW	22,00
230V - I+N			NO
230V - III		OPC3x16+T-80 A	
400V - III+N		4x6+T - 50 A	

WATER

Water consumption (lit/h)			336,00
Pressure (Kg/cm2)			2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) **60,00**

NORMAL SPIN WASHER EXTRACTOR, LN-35 M E

Hardmount machine.
 Elements not included.
 Machine must be fixed to the floor.
 Stainless steel construction.
 Capacity: 35 Kg(1:10).
 Integrated standard microprocessor
 16 standard washing programs.
 Any of them can be selected as the standard one.
 Configurable water levels +10 % ÷ - 10%.
 It is possible to configure the times and temperatures of each phase, as well as to cancel them.
 Phase monitoring thanks to 8 LED indicators.
 7-segment display with 4 digits.
 Up to 4 dosage signals.
 Possibility to install one automatic detergent doser on the rear of the machine.
 Detergent deposit with 4 compartments (pre-wash, wash, bleachers and softeners).
 Safety switch for door opening.
 Motor with frequency variator incorporated.
 Drum diameter: 860 mm.
 Drum depth: 602 mm.
 Door diameter: 560 mm.
 Spin speed: 458 r.p.m.
 G Factor: 100.
 WRAS approved product.
 ETL certified product.
 Heating system: Electric.
 Heating power: 21 kW.
 Total power: 22 kW.
 Dimensions: 979 x 1.166 x 1.428 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	

