



### Washer extractors

#### Normal Spin washer extractors

## NORMAL SPIN WASHER EXTRACTOR, LN-35 M V

### DIMENSIONS

		Article	Packed
Length	mm	979,00	1.020,00
Depth	mm	1.166,00	1.240,00
Height	mm	1.428,00	1.680,00
Weigth	Kg	473,00	503,00
Volumen	m3	1,63	2,12

### ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5+T - 16 A
230V - III		
400V - III+N		

### WATER

Water consumption (lit/h)		336,00
Pressure (Kg/cm2)		2 - 4

### GAS

Not used

### STEAM

Consumption	kg/h	35,00
Pressure	bar	2 - 4

### AIR

Not used

### LEVEL SOUND

(dB) 60,00

### NORMAL SPIN WASHER EXTRACTOR, LN-35 M V

Hardmount machine.  
Elements not included.  
Machine must be fixed to the floor.  
Stainless steel construction.  
Capacity: 35 Kg(1:10).  
Integrated standard microprocessor  
16 standard washing programs.  
Any of them can be selected as the standard one.  
Configurable water levels +10 % ÷ - 10%.  
It is possible to configure the times and temperatures of each phase, as well as to cancel them.  
Phase monitoring thanks to 8 LED indicators.  
7-segment display with 4 digits.  
Up to 4 dosage signals.  
Possibility to install one automatic detergent doser on the rear of the machine.  
Detergent deposit with 4 compartments (pre-wash, wash, bleachers and softeners).  
Safety switch for door opening.  
Motor with frequency variator incorporated.  
Drum diameter: 860 mm.  
Drum depth: 602 mm.  
Door diameter: 560 mm.  
Spin speed: 458 r.p.m.  
G Factor: 100.  
WRAS approved product.  
ETL certified product.  
Heating system: Steam with pressure 2-4 kg/cm2.  
Total electric power: 3,00 kW.  
Dimensions: 979 x 1.166 x 1.428 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	
STEAM Inlet	840	0	1.010	3/4"	

