



**Washer extractors**

**Fast Spin washer extractors**

**FAST SPIN WASHER, LR-10 M V**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>692,00</b>	<b>730,00</b>
Depth	mm	<b>830,00</b>	<b>1.000,00</b>
Height	mm	<b>1.177,00</b>	<b>1.410,00</b>
Weigth	Kg	<b>208,00</b>	<b>216,00</b>
Volumen	m3	<b>0,68</b>	<b>1,03</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V -1+N		<b>0,75</b>
230V - III		<b>2x1,5+T-6A</b>
400V - III+N		<b>NO</b>
		<b>NO</b>

**WATER**

Water consumption (lit/h)		<b>135,00</b>
Pressure (Kg/cm2)		<b>2 - 4</b>

**GAS**

Not used

**STEAM**

Consumption	kg/h	<b>30,00</b>
Pressure	bar	<b>2 _ 4</b>

**AIR**

Not used

**LEVEL SOUND**

(dB) **60,00**

**FAST SPIN WASHER EXTRACTOR, LR-10 M V**

Hardmount machine.  
 Stainless steel construction.  
 Capacity: 10 Kg(1:10).  
 Electronic microprocessor control.  
 16 standard programs with 42 possible variations.  
 Option to select any of the 16 preconfigured as standard, using the amount of cycles decided.  
 Option to modify for all the cycles, the temperature or time of each face, even removing any face.  
 Adjustable water levels +10 / -10 % .  
 Four digital display (7 LED segments).  
 Phase program indicator by LED in progress.  
 Detergent dispenser with 4 compartments(rewash, wash, bleach and softener).  
 Pre set for up to 4 external liquid detergent pumps.  
 Door safety system.  
 Drum diameter: 532 mm.  
 Drum depth: 425 mm.  
 Door diameter: 290 mm.  
 Incorporate speed control for the motor.  
 Unbalancing control system trough the speed control.  
 Spin speed: 820 r.p.m.  
 G Factor: 200  
 Easy to attach automatic dispenser at rear of machine. (dispenser not included)  
 Water consumption in program n° 2 60°: 118 litres.  
 Fully equipped with all the necessary components to fix the machine to the floor. (needed).  
 Heating system: Steam with pressure 2-4 kg/cm2.  
 Total power: 0,75 Kw.  
 Dimensions: 692 x 830 x 1.177 mm.

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	106	0	871		0
DRAIN	252	0	80	2"	
COLD WATER	623	0	1.070	3/4"	
HOT WATER	468	0	1.050	3/4"	
STEAM Inlet	647	0	775	1/2"	

