



### Washer extractors

#### Fast Spin washer extractors

## FAST SPIN WASHER, LR-13 M V

### DIMENSIONS

		Article	Packed
Length	mm	790,00	830,00
Depth	mm	870,00	1.010,00
Height	mm	1.321,00	1.560,00
Weigth	Kg	225,00	255,00
Volumen	m3	0,91	1,31

### ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5+T-10A
230V - III		NO
400V - III+N		NO

### WATER

Water consumption (lit/h)		168,00
Pressure (Kg/cm2)		2 - 4

### GAS

Not used

### STEAM

Consumption	kg/h	30,00
Pressure	bar	2 _ 4

### AIR

Not used

### LEVEL SOUND

(dB) 60,00

### FAST SPIN WASHER EXTRACTOR, LR-13 M V

Hardmount machine.

Stainless steel construction.

Capacity: 13 Kg(1:10).

Electronic microprocessor control.

16 standard programs with 42 possible variations.

Option to select any of the 16 preconfigured as standard, using the amount of cycles decided.

Option to modify for all the cycles, the temperature or time of each face, even removing any face.

Adjustable water levels +10 / -10 % .

Four digital display (7 LED segments).

Phase program indicator by LED in progress.

Detergent dispenser with 4 compartments(prewash, wash, bleach and softener).

Pre set for up to 4 external liquid detergent pumps.

Door safety system.

Drum diameter: 620 mm.

Drum depth: 430 mm.

Door diameter: 373 mm.

Incorporate speed control for the motor.

Unbalancing control system trough the speed control.

Spin speed: 760 r.p.m.

G Factor: 200

Easy to attach automatic dispenser at rear of machine. (dispenser not included)

Water consumption in program n° 2 60°: 168 litres.

Fully equipped with all the necessary components to fix the machine to the floor. (needed).

Heating system: Steam with pressure 2-4 kg/cm2.

Total power: 1,5 Kw.

Dimensions: 790 x 870 x 1.321 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	108	0	1.022		0
DRAIN	269	0	80	2"	
COLD WATER	714	0	1.216	3/4"	
HOT WATER	554	0	1.196	3/4"	
STEAM Inlet	743	0	900	1/2"	

