



**Washer extractors**

**Fast Spin washer extractors**

**FAST SPIN WASHER, LR-25 M V**

**DIMENSIONS**

		Article	Packed
Length	mm	885,00	930,00
Depth	mm	1.127,00	1.240,00
Height	mm	1.428,00	1.680,00
Weigth	Kg	320,00	350,00
Volumen	m3	1,42	1,94

**ELECTRICITY**

			KW
<u>Electric power</u>			3,00
230V -1+N		2x1,5+T-16A	
230V - III		OPC3x1,5+T-10 A	
400V - III+N		4x1,5+T - 6 A	

**WATER**

Water consumption (lit/h)		336,00
Pressure (Kg/cm2)		2 - 4

**GAS**

Not used

**STEAM**

Consumption	kg/h	30,00
Pressure	bar	2_4

**AIR**

Not used

**LEVEL SOUND**

(dB) 60,00

**FAST SPIN WASHER EXTRACTOR, LR-25 M V**

Hardmount machine.  
 Stainless steel construction.  
 Capacity: 25 Kg(1:10).  
 Electronic microprocessor control.  
 16 standard programs with 42 possible variations.  
 Option to select any of the 16 preconfigured as standard, using the amount of cycles decided.  
 Option to modify for all the cycles, the temperature or time of each face, even removing any face.  
 Adjustable water levels +10 / -10 % .  
 Four digital display (7 LED segments).  
 Phase program indicator by LED in progress.  
 Detergent dispenser with 4 compartments(rewash, wash, bleach and softener).  
 Pre set for up to 4 external liquid detergent pumps.  
 Door safety system.  
 Drum diameter: 700 mm.  
 Drum depth: 670 mm.  
 Door diameter: 373 mm.  
 Incorporate speed control for the motor.  
 Unbalancing control system trough the speed control.  
 Spin speed: 715 r.p.m.  
 G Factor: 200  
 Easy to attach automatic dispenser at rear of machine. (dispenser not included)  
 Water consumption in program n° 2 60°: 336 litres.  
 Fully equipped with all the necessary components to fix the machine to the floor. (needed).  
 Heating system: Steam with pressure 2-4 kg/cm2.  
 Total power: 3 Kw.  
 Dimensions: 885 x 1.127 x 1.428 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	80	3"	
COLD WATER	815	0	1.320	3/4"	
HOT WATER	660	0	1.300	3/4"	
STEAM Inlet	840		1.010	3/4"	

