



Tumble Dryers

Tumble Dryers Economic Line

TUMBLE DRYER, SC/E-10 ECONOMIC LINE

DIMENSIONS

		Article	Packed
Length	mm	785,00	880,00
Depth	mm	857,00	955,00
Height	mm	1.700,00	1.840,00
Weigth	Kg	170,00	200,00
Volumen	m3	1,14	1,55

ELECTRICITY

Electric power	KW	
230V -1+N		12,43
230V - III		NO
400V - III+N		3x6+T - 50 A
		4x4+T - 25 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 64,00

TUMBLE DRYER, SC/E-10 ECONOMIC LINE

Load Capacity : 12 kg. (load factor 1:18) or 10 kg (load factor 1:22).

Production: 18 ÷ 22 kg/h.

Galvanized steel body.

Axial airflow.

Time selector.

Temperature selector.

COOL DOWN at end of cycle.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 870 m3/h.

Drum in galvanized steel.

IMPORTANT: Reversing drum .

Drum diameter: 750 mm

Depth of drum: 475 mm

Diameter of door: 574 mm.

reversible door hanging.

Fluff filter in lower part .

Transmission by means of motoreducer.

Main heating system: electric.

Electrical connection : 400 V - III+N+ GROUND - 50/60 Hz.

Heating power: 12 kW.

Total power: 12,43 kW.

Dimensions: 785 x 857 x 1700 mm

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	528	0	821		0
EXHAUST	558	0	169	200 mm.	

