



Laundry for Self-Service

Tumble Dryers for self service

STACK TUMBLE DRYER, SD/G-2x14 MCP

DIMENSIONS

		Article	Packed
Length	mm	756,00	825,00
Depth	mm	1.114,00	1.200,00
Height	mm	1.988,00	2.100,00
Weigth	Kg	247,00	264,00
Volumen	m3	1,67	2,02

ELECTRICITY

Electric power		KW	0,50
230V - 1+N			
230V - III			
400V - III+N			

WATER

Not used

GAS

Power		KW	20,00
		Kcal/h	17.200,00
LPG	Consumption (kg/h)		0,00
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		0,00
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 64,00

STACK TUMBLE DRYER, SD/G-2x14 MCP

Load Capacity :2 x 14 Kg

Outer casing made of white-enamelled steel.

Double column model, what allows a great use of the space: in the space of one machine it is possible to fit two of 14 kg.

Model prepared for the prepayment card and the payment central unit.

It is very easy to change and adjust the price of the operations.

MP programmer and the possibility to configure consecutive short programs depending on the inserted coins or tokens.

Temperature and drying cycle time control.

Temperature and time digital display. Cycle indicators.

Axial air flow (less space required, great efficiency)

Fluff compartment and filter in the central part.

Lockable filter cap.

Safety mike in case the door opens.

Door with a useful Ø of: 546 mm.

Galvanized steel drum. Volume: 286 litres.

Drum: Ø 692 x 762 mm.

Electrical connections and independent extractions for each machine.

Main heating system: Gas.

Electrical connection : 230 V - 1PH + N + GROUND.

Gas power: 2 x 20 KW

Dimensions: 756 x 1.114 x 1.988 mm

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	58	0	1.859		
ELECTRICITY	58	0	905		
EXHAUST	792	161	1.585	203 mm.	
GAS	64	312	1.912	1/2	

