



Ironer

**Ironer**

**PSG-100/330**

<u>Dimensions*</u>		<u>Machine*</u>	<u>Package*</u>		
Width*	mm	4490	4570	Roll diameter mm	1000
Depth*	mm	2090	2280	Working width mm	3300
High*	mm	2430	2400	Maximum production	250-290 Kg/h**
Weight*	Kg	3700	4250	Ironing speed adjustable from	4-18 mt/min
Volume*	m <sup>3</sup>	22,80	25,01	Smokes extraction built-in system	2x1000 m <sup>3</sup> /h
				Electrical, steam, natural gas and LPG heating	
				Touch- screen control panel	
				Ironing belts	
				Safety hands bar device	
				Alarm advises on keyboard	
				Fans self-cleaning	

<u>Length folds</u>		<u>Crossfold</u>		
Lanes	Folds	Lanes	Folds	
-	-	-	-	
-	-	-	-	

**Optional (to define at the order)**

- √ Vacuum table
- √ Automatic feeder (vacuum table included)
- √ Small items stacker with 2 lines
- √ Small items stacker with 4 lines
- √ Rear exit
- √ Supply different than 400V ~3N + T 50Hz


**Electrical installation\***

Electrical power	Kw	2,6 *
Voltage 400V ~3N + T	A	3,8 *
Voltage 230V ~3 + T	A	6,5 *

**Pneumatic installation\***

Compressed air needed bar	6,5	5000	NI/h
---------------------------	-----	------	------

<u>Connections</u>	<u>Compressed air</u>	<u>Electricity</u>	<u>Gas/Steam</u>	<u>Exhaust fume</u>	<u>Exhaust (Steam)</u>
Type	Ø 12 mm	5G4-400V	1" / 1 -1/4"	2x120 mm	1"
X mm	150	40	190	186 / 4128	110
Y mm	0	0	0	152	0
Z mm	85	135	750	2160	750



**Heating**

<u>Natural gas</u>		<u>LPG</u>		<u>Steam (P max 12 bar)</u>		<u>Electrical</u>					
Consumption	m <sup>3</sup> /h	16,50	Consumption	m <sup>3</sup> /h	5,90	Consumption	Kg/h	260	Consumption	A	130
Power	Kw	155,70	Power	Kw	159,10	Power	Kw	150	Power	Kw	90

\*) Optional excluded

\* \*) 50% residual humidity, 140 gr/m<sup>2</sup> cotton, used roll surface 100% - The technical data can change without advice