



Ironer

**Ironer**

**PS-60/260**

<u>Dimensions*</u>		<u>Machine*</u>		<u>Package*</u>		
Width*	mm	3670	3830	Roll diameter mm		600
Depth*	mm	1440	1620	Working width mm		2600
High*	mm	2030	1960	Maximum production		75-105 Kg/h**
Weight*	Kg	1800	2050	Ironing speed adjustable from		3-10 mt/min
Volume*	m <sup>3</sup>	10,73	12,16	Smokes extraction built-in system		2x1000 m <sup>3</sup> /h
				Electrical, steam, natural gas and LPG heating		
				Touch- screen control panel		
				Ironing belts		
				Safety hands bar device		
				Alarm advises on keyboard		
				Fans self-cleaning		

<u>Length folds</u>		<u>Crossfold</u>	
Lanes	Folds	Lanes	Folds
-	-	-	-
-	-	-	-

**Optional (to define at the order)**

- √ Vacuum table
- √ Automatic feeder (vacuum table included)
- √ Small items stacker with 2 lines
- √ Small items stacker with 4 lines
- √ Rear exit
- √ Supply different than 400V ~3N + T 50Hz


**Electrical installation\***

Electrical power	Kw	1,9 *
Voltage 400V ~3N + T	A	2,7 *
Voltage 230V ~3 + T	A	4,8 *

**Pneumatic installation\***

Compressed air needed bar	6,5	5000	NI/h
---------------------------	-----	------	------

<u>Connections</u>	<u>Compressed air</u>	<u>Electricity</u>	<u>Gas/Steam</u>	<u>Exhaust fume</u>	<u>Exhaust (Steam)</u>
Type	Ø 12 mm	5G4-400V	1"	2x120 mm	½"
X mm	150	40	190	186 / 3428	110
Y mm	0	0	0	152	0
Z mm	85	135	885	1800	885



**Heating**

<u>Natural gas</u>		<u>LPG</u>		<u>Steam (P max 12 bar)</u>		<u>Electrical</u>					
Consumption	m <sup>3</sup> /h	6,70	Consumption	m <sup>3</sup> /h	2,50	Consumption	Kg/h	95	Consumption	A	78
Power	Kw	63,30	Power	Kw	67,40	Power	Kw	55	Power	Kw	54

\*) Optional excluded

\* \*) 50% residual humidity, 140 gr/m<sup>2</sup> cotton, used roll surface 100% - The technical data can change without advice