



Ironer

Ironer

PS-80/260

<u>Dimensions*</u>		<u>Machine*</u>	<u>Package*</u>		
Width*	mm	3790	3900	Roll diameter mm	800
Depth*	mm	1770	2280	Working width mm	2600
High*	mm	2200	2140	Maximum production	140-175 Kg/h**
Weight*	Kg	2350	2700	Ironing speed adjustable from	3-13 mt/min
Volume*	m ³	14,76	19,03	Smokes extraction built-in system	2x1000 m ³ /h
				Electrical, steam, natural gas and LPG heating	
				Touch- screen control panel	
				Ironing belts	
				Safety hands bar device	
				Alarm advises on keyboard	
				Fans self-cleaning	

<u>Length folds</u>		<u>Crossfold</u>	
Lanes	Folds	Lanes	Folds
-	-	-	-
-	-	-	-

Optional (to define at the order)

- √ Vacuum table
- √ Automatic feeder (vacuum table included)
- √ Small items stacker with 2 lines
- √ Small items stacker with 4 lines
- √ Rear exit
- √ Supply different than 400V ~3N + T 50Hz


Electrical installation*

Electrical power	Kw	2,2 *
Voltage 400V ~3N + T	A	3,2 *
Voltage 230V ~3 + T	A	5,5 *

Pneumatic installation*

Compressed air needed bar	6,5	5000	NI/h
---------------------------	-----	------	------

<u>Connections</u>	<u>Compressed air</u>	<u>Electricity</u>	<u>Gas/Steam</u>	<u>Exhaust fume</u>	<u>Exhaust (Steam)</u>
Type	Ø 12 mm	5G4-400V	1"	2x120 mm	½"
X mm	150	40	190	186 / 3428	110
Y mm	0	0	0	152	0
Z mm	85	135	750	1966	750



Heating

<u>Natural gas</u>		<u>LPG</u>		<u>Steam (P max 12 bar)</u>		<u>Electrical</u>					
Consumption	m ³ /h	9,20	Consumption	m ³ /h	3,40	Consumption	Kg/h	150	Consumption	A	104
Power	Kw	86,95	Power	Kw	91,70	Power	Kw	85	Power	Kw	72

*) Optional excluded

* *) 50% residual humidity, 140 gr/m² cotton, used roll surface 100% - The technical data can change without advice