



Ironer Folder

Ironer with length folds system

PS-80/260 PL

<u>Dimensions*</u>		<u>Machine*</u>	<u>Package*</u>		
Width*	mm	3790	3950	Roll diameter mm	800
Depth*	mm	1770	2220	Working width mm	2600
High*	mm	2200	2140	Maximum production	140-175 Kg/h**
Weight*	Kg	2535	2885	Ironing speed adjustable from	3-13 mt/min
Volume*	m ³	14,76	18,77	Smokes extraction built-in system	2x1000 m ³ /h

<u>Length folds</u>		<u>Crossfold</u>	
Lanes	Folds	Lanes	Folds
1	1-2	-	-
2	1-2	-	-

Electrical, steam, natural gas and LPG heating
Touch- screen control panel
Ironing belts
Safety hands bar device
Alarm advises on keyboard
Fans self-cleaning
Ironing/folding chance at the same time on 2 independ
Program.logic control (PLC) that allows to fold
the linen according to its dimensions and to create 20 working programs
Totally personalized folding parameters

Optional (to define at the order)

- √ Vacuum table
- √ Automatic feeder (vacuum table included)
- √ Small items stacker with 2 lines
- √ Small items stacker with 4 lines
- √ By-pass length folds
- √ Supply different than 400V ~3N + T 50Hz
- √ Remote service
- √ Double pressure on length folds
- √ Dirty and ripped linen reject
- √ Rear exit (by-pass included)


Electrical installation*

Electrical power	Kw	2,2 *
Voltage 400V ~3N + T	A	3,2 *
Voltage 230V ~3 + T	A	5,5 *

Pneumatic installation*

Compressed air needed bar	6,5	9000	NI/h
---------------------------	-----	------	------

<u>Connections</u>	<u>Compressed air</u>	<u>Electricity</u>	<u>Gas/Steam</u>	<u>Exhaust fume</u>	<u>Exhaust (Steam)</u>
Type	Ø 12 mm	5G4-400V	1"	2x120 mm	½"
X mm	150	40	190	186 / 3428	110
Y mm	0	0	0	152	0
Z mm	85	135	750	1966	750



Heating

<u>Natural gas</u>		<u>LPG</u>		<u>Steam (P max 12 bar)</u>		<u>Electrical</u>					
Consumption	m ³ /h	9,20	Consumption	m ³ /h	3,40	Consumption	Kg/h	150	Consumption	A	104
Power	Kw	86,95	Power	Kw	91,70	Power	Kw	85	Power	Kw	72

*) Optional excluded

* *) 50% residual humidity, 140 gr/m2 cotton, used roll surface 100% - The technical data can change without advice