



Refrigeration

Blast chillers & freezers

**REMOTE UNIT FOR BLAST CHILLERS,
UCS-424**

DIMENSIONS

		Article	Packed
Length	mm	935,00	935,00
Depth	mm	700,00	700,00
Height	mm	575,00	575,00
Weigth	Kg	92,00	100,00
Volumen	m3	0,38	0,40

ELECTRICITY

Electric power	KW	
230V -1+N		2x2,5 - 25 A.
230V - III		
400V - III+N		

WATER

Water consumption (lit/h)		0,00
Pressure (Kg/cm2)		

GAS

Not used

STEAM

Not used

AIR

Not used

REMOTE UNIT FOR BLAST CHILLERS, UCS-424

Recommended unit for blast chillers models:

- CS-201
- CS-201-D

Provided with all the components fixed on a baseplate: compressor, condenser, fan, desecant filter and capillary tube.

Refrigerant charge is not included.

The tube for the connection is not included.

Refrigerant gas: R-404 A

Voltage: 230 V - 1N - 50/60 Hz.

Refrigeration power: 6,42 kW.

Consumption: 3,3 kW.

Dimensions: 935 x 700 x 575 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	0	0	0		

