



Refrigeration

Blast chillers & freezers

**REMOTE UNIT FOR BLAST CHILLERS,
UCS-528**

DIMENSIONS

		Article	Packed
Length	mm	1.004,00	1.004,00
Depth	mm	700,00	700,00
Height	mm	650,00	650,00
Weigth	Kg	120,00	130,00
Volumen	m3	0,46	0,46

ELECTRICITY

Electric power	KW	
230V -1+N		2x4 - 32 A.
230V - III		
400V - III+N		

WATER

Water consumption (lit/h)		0,00
Pressure (Kg/cm2)		

GAS

Not used

STEAM

Not used

AIR

Not used

REMOTE UNIT FOR BLAST CHILLERS, UCS-528

Recommended unit for powered blast chillers models:

- CSP-201
- CSP-201-D

Provided with all the components fixed on a baseplate: compressor, condenser, fan, desecant filter and capillary tube.

Refrigerant charge is not included.

The tube for the connection is not included.

Refrigerant gas: R-404 A

Voltage: 230 V - 1N - 50/60 Hz.

Refrigeration power: 9,62 kW.

Consumption: 4,74 kW.

Dimensions: 1.004 x 700 x 650 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	0	0	0		

