



Refrigeration

Blast chillers & freezers

**REMOTE UNIT FOR BLAST CHILLERS,
UCS-842**

DIMENSIONS

		Article	Packed
Length	mm	1.004,00	1.004,00
Depth	mm	700,00	700,00
Height	mm	650,00	650,00
Weigth	Kg	138,00	150,00
Volumen	m3	0,46	0,46

ELECTRICITY

Electric power	KW	
230V -1+N		4,82
230V - III		
400V - III+N		4x1,5 + 16 A.

WATER

Water consumption (lit/h)		0,00
Pressure (Kg/cm2)		

GAS

Not used

STEAM

Not used

AIR

Not used

REMOTE UNIT FOR BLAST CHILLERS, UCS-842

Recommended unit for blast chillers models:

- CS-202
- CS-202-D

Provided with all the components fixed on a baseplate: compressor, condenser, fan, desecant filter and capillary tube.

Refrigerant charge is not included.

The tube for the connection is not included.

Refrigerant gas: R-404 A

Voltage: 400 V - 3+N - 50/60 Hz.

Refrigeration power: 11,3 kW.

Consumption: 4,82 kW.

Dimensions: 1.004 x 700 x 650 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	0	0	0		

