



Catalogue
CATERING

Chapter
DISTRIBUTION

Model
CCHF-10 230V 1N 50/60Hz

19044546

DIMENSIONS

	Article		Packed	
Lenght	790	mm	1085	mm
Depth	935	mm	940	mm
Height	1215	mm	1315	mm
Weight	80,000	kg	90,000	kg
Volume	1,341	m3	1,341	m3

ELECTRICITY

Electric power		2,00	kw
Voltage			230V -1N
Single-phase 230V wiring			2X1,5 - 10 A
Frequency		50/60	hz

HOT TROLLEY WITH HUMIDITY CONTROL, CCHF-10

Modern and intuitive electronic control panels.

Double walled sides and door, insulated with high density polyurethane, giving great robustness and firmness.

Recessed monoblock guides with wide radii, guaranteeing maximum hygiene.

Efficient heat production system composed of heating element and fan.

Recessed water reservoir with rounded corners. The heat is produced by a highperformance silicon heating element.

4-level humidity regulation system to adapt to the different products kept inside. The humidity system can also be fully switched off, reducing energy consumption.

The 270° opening door offers users maximum freedom of movements and safety during daily use, increasing comfort and well-being during work operations.

The inner door panel is completely smooth and free from any elements that might prevent thorough cleaning.

No heat loss. Door seal fixed to the frame of the structure. Can be replaced easily without the need for tools.

The whole perimeter is protected by a bumper, manufactured in resistant, non-marking material.

Pivoting wheels, 2 with brakes.

Manufactured completely in AISI-304 stainless steel.

Heat system designed to reach the operational temperature in a very short space of time.

Electronic membrane keypad and digital display.

Ergonomic latch with lock.

Modern, elegant and very robust design.

Operational temperature 30 °C to 90 °C.

Storage of GN 2/1 y GN 1/1 trays with depth of up to 65 mm.

1 door.

10 GN-2/1 levels, 70 mm separation.

Power: 2.000 W.

Dimensions: 790 x 935 x 1.215 mm.



Catalogue
CATERING

Chapter
DISTRIBUTION

Model
CCHF-10 230V 1N 50/60Hz

19044546

