



Catalogue
CATERING
Chapter
REFRIGERATION

Model
EAF-702 P 230V 1N 50Hz

19038535

28/08/2019

REFRIGERATION CABINET WITH FISH COMPARTMENT CONCEPT, EAF-702 P

- Constructed in AISI-304 stainless steel.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
- Built-in drainage to get rid of waste liquids inside the unit.
- Height adjustable stainless steel legs.
- Inner LED lights.
- 50 mm, 40 kg/m³ injected polyurethane insulation.
- Removable and height adjustable plastic covered steel shelves (17 Snack size levels) for easy cleaning. Equipment: 3 shelves per large door.
- Forced draught cooling system.
- Working temperature: from -2 °C to +8 °C. Ambient temperature: 43 °C (Except specific intensive usage).
- Number of doors: 2

FISH COMPARTMENT:


- Equipment: 3 drawers in sanitary PVC with perforated stainless steel floor.
- Independent hermetic compressor with ventilated condenser.
- Refrigerante ecológico.
- Environmentally-friendly refrigerant.
- Drainage pipe from the chamber to connect to exterior drain.
- Operational temperature: -4 °C, -1 °C.

Options:

- Castor kit (factory assembly).
- "- Stainless steel back panel.
- "

DIMENSIONS

X Width	693 mm	X Gross width	780 mm
Y Depth	726 mm	Y Gross depth	800 mm
Z Height	2067 mm	Z Gross height	2084 mm
Net Weight	129,0 kg	Gross Weight	135,0 kg
Net volume	1,040 m ³	Gross volume	1,300 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,654 kW
Voltage	230V - 1N
Amperage	0
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-290
----------	-------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,250 kW
Annual elec. consumption	679,00 kWh
Power consumption 24h	1,86 kWh
Gross internal volume	506 L
Refrigeration net.vol	193 L
Climate class	4
Cooling gas load	98,000 g
Clasif. Energy efficiency	D
Energy Efficiency Index	73,34 %
Model type	Vertical cabinet

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------



Catalogue
CATERING

Chapter
REFRIGERATION

Model
EAF-702 P 230V 1N 50Hz

19038535

28/08/2019

